

Ria Thompson, DenDesignery +647 500 6518 ria@dendesignery.com www.dendesignery.com

### 1 MAIN DETAILS

PROJECT DETAILS						
NAME: 3-Bedroom Detached House Show	Home	SITE ADDRESS: <site address=""></site>			<b>LIENT N</b> client na	
				-		
CONTRACTOR DETAILS						
NAME:	ADDRE		PHONE			E-MAIL:
<contractor's name=""></contractor's>	<contra< td=""><td>actor's address &gt;</td><td>office: &lt;###&gt;</td><td>mobile: &lt;##/&gt;</td><td></td><td><contractor's e-mail=""></contractor's></td></contra<>	actor's address >	office: <###>	mobile: <##/>		<contractor's e-mail=""></contractor's>

1/	Please review this specification, the reference drawings and schedules and contact me as soon as possible with any issues or questions.
1/	Flease review this specification, the reference of awings and schedules and contact the as soon as possible with any issues or questions.
2/	This specification provides a list of all kitchen furnishings that are to be installed along with their relevant details, as well as product details and instructions for installing the backsplash. For exact placement of all items the following drawings are to be referred to closely: (D11) Kitchen Elevation K1, (D12) Kitchen Elevation K2, (D1) Furnishing Layout – Ground Floor(Kitchen). All main kitchen items listed in this document are ID-ed by numbers in the same way as in the above mentioned drawings for easy cross referencing.
3/	Important scheduling note for coordination with the flooring and the painter/decorator contractors: The kitchen must be installed after all painting/wallpapering and the subsequent flooring installation have been completed.
1/	Please carry out all work with appropriate care taken so that no damage is inflicted on the newly installed floors and wall coverings.
5/	No substitutions are to be made unless agreed upon ahead of time.
6/	The specific manufacturer's instructions are to be followed in each case.
7/	As much as possible, please leave the work areas in a tidy fashion at the end of each day. All rubbish is to be promptly removed from the site.



Ria Thompson, DenDesignery +647 500 6518 ria@dendesignery.com www.dendesignery.com

#### **2 BASE CABINETS \***

PRODU	CT DETAILS	<u>5</u>	_			_	_		
Ref ID within room	TYPE	QUANTITY	BRAND / SUPPLIER	NAME	CODE / REF	COLOUR / FINISH	DIMS INFO (mm)	REFERENCE DRAWING(S) for PLACEMENT	INSTALLATION NOTES and WWW LINKS  Please assemble and install according to the product manual that accompanies each product.
3	Base cabinet with wire basket/ drawer/ door	1	IKEA	AKURUM	Article Number: 198.927.03 Cabinet number: AK BDW1	Frame: White Front: Abstrakt High gloss cream	Width: 455 Depth: 628 Height: 770	(D11) Kitchen Elevation K1, (D1) Furnishing Layout – Ground Floor (Kitchen)	Product info: http://www.ikea.com/ca/en/catalog/products/ S69863581/#/S19892703 Requires 2 KANSLI handles – Small (Please see Section 4).
4	Base cabinet for sink with 2 doors/2 panels	1	IKEA	AKURUM	Article Number: 398.928.39 Cabinet number: AK SD	Frame: White Front: Abstrakt High gloss cream	Width: 760 Depth: 630 Height: 770	(D11) Kitchen Elevation K1, (D1) Furnishing Layout – Ground Floor (Kitchen)	Product info:  http://www.ikea.com/ca/en/catalog/products/ S39869626/#/S39892839  Requires 2 KANSLI handles - Small (Please see Section 3).  To be installed with BOHOLMEN bowl inset sink, and LAGAN single lever kitchen faucet (Please see items ID17 & ID18 in Section 7 - Plumbing)
5	Corner base cabinet with carousel	2	IKEA	AKURUM	Article Number: 898.927.47 Cabinet number: AK CBC	Frame: White Front: Abstrakt High gloss cream	Width: 935 Frame width& depth: 940 Height: 771	(D1) Furnishing Layout – Ground Floor (Kitchen), (D11) Kitchen Elevation K1, (D12) Kitchen Elevation K2	Product info:  http://www.ikea.com/ca/en/catalog/products/ S49869715/#/S89892747  Each requires 1 KANSLI handle - Small (Please see Section 4)

<sup>\*</sup>All base cabinets are to be installed with AKURUM Legs and PERFEKT GNOSJÖ Plinth (Please see Section 3 Accessories for Base Cabinets)



Ria Thompson, DenDesignery +647 500 6518 ria@dendesignery.com www.dendesignery.com

#### 2 BASE CABINETS \* - continued

PRODU	CT DETAILS	<u> </u>							
Ref ID within room	TYPE	QUANTITY	BRAND / SUPPLIER	NAME	CODE / REF	COLOUR / FINISH	DIMS INFO (mm)	REFERENCE DRAWING(S) for PLACEMENT	INSTALLATION NOTES and WWW LINKS  Please assemble and install according to the product manual that accompanies each product.
6	Base cabinet with 3 drawers	1	IKEA	AKURUM	Article Number: 398.926.79 Cabinet number: AK B4D	Frame: White Front: Abstrakt High gloss cream	Width: 608 Depth: 610 Height: 770	(D12) Kitchen Elevation K2, (D1) Furnishing Layout – Ground Floor (Kitchen)	Product info: http://www.ikea.com/ca/en/catalog/products/ S99869647/#/S79892677 Requires 3 KANSLI handles – Large (Please see Section 4)
7	Base cabinet with shelves	1	IKEA	AKURUM	Article Number: 298.926.65 Cabinet number: AK B1	Frame: White Front: Abstrakt High gloss cream	Width: 608 Depth: 610 Height: 770	(D12) Kitchen Elevation K2, (D1) Furnishing Layout – Ground Floor (Kitchen)	Product info:  http://www.ikea.com/ca/en/catalog/products/ S19869590/#/S29892665  Requires 1 KANSLI handle – Large (Please see Section 4)
8	Base cabinet for oven	1	IKEA	AKURUM	Article Number: 098.927.13 Cabinet number: AK BO	Frame: White Front: Abstrakt High gloss cream	Width: 760 Depth: 630 Height: 770	(D1) Furnishing Layout – Ground Floor (Kitchen)	Product info:  http://www.ikea.com/ca/en/catalog/products/ S49869621/#/S09892713  To be Installed with oven DÅTID (Please see item ID14 in Section 6 - Appliances). Ceramic cooktop NUTID (item ID15 in Section 6) will be installed above the oven after the countertops have been fitted.  Requires cover panels for exposed right and back sides. For details please see Section 5 - COVER PANELS for EXPOSED SIDES of PENINSULA CABINETS, Cover Panel - to be cut to size.

<sup>\*</sup>All base cabinets are to be installed with AKURUM Legs and PERFEKT GNOSJÖ Plinth (Please see Section 4 Accessories for Base Cabinets)



Ria Thompson, DenDesignery +647 500 6518 ria@dendesignery.com www.dendesignery.com

### 3 WALL CABINETS and SHELVES

PRODU	ICT DETAILS	<u> </u>							
Ref ID within	TYPE	QUANTITY	BRAND / SUPPLIER	NAME	CODE / REF	COLOUR / FINISH	DIMS INFO	REFERENCE DRAWING(S)	INSTALLATION NOTES and WWW LINKS
room							,	for PLACEMENT	Please assemble and install according to the product manual that accompanies each product.
9	Wall cabinet horizontal - Small	1	IKEA	AKURUM	Article Number: 198.928.97 Cabinet number: AK WH	Frame: White Front: Abstrakt High gloss cream	Width: 767 Depth: 330 Height: 380	(D11) Kitchen Elevation K1, (D1) Furnishing Layout – Ground Floor (Kitchen)	Product info:  http://www.ikea.com/ca/en/catalog/products/ S79867296/#/S19892897  Requires 1 KANSLI handle - Large (Please see Section 4).  To be mounted to the wall using a suspension rail cut to size (Please see Section 4).
10	Wall cabinet horizontal - Large	5	IKEA	AKURUM	Article Number: 798.928.99 Cabinet number: AK WH	Frame: White Front: Abstrakt High gloss cream	Width: 990 Depth: 330 Height: 375	(D12) Kitchen Elevation K2, (D1) Furnishing Layout – Ground Floor (Kitchen)	Product info:  http://www.ikea.com/ca/en/catalog/products/ S79867296/#/S79892899  Each requires 1 KANSLI handle - Large (Please see Section 4). To be mounted to the wall using a suspension rail cut to size (Please see Section 4).
11	Wall Shelf	6	IKEA	LIMHAMN	Article Number : 401.777.18	Stainless steel	Width: 600 Depth: 200 Height: 70	(D11) Kitchen Elevation K1, (D12) Kitchen Elevation K2, (D1) Furnishing Layout - Ground Floor (Kitchen)	Product info:  http://www.ikea.com/ca/en/catalog/products/ 00177715/#/40177718



Ria Thompson, DenDesignery +647 500 6518 ria@dendesignery.com www.dendesignery.com

#### 4 ACCESSORIES for BASE and WALL CABINETS

PRODUCT D	<u>ETAILS</u>						
TYPE	QUANTITY	BRAND / SUPPLIER	NAME	CODE / REF	COLOUR / FINISH	DIMS INFO (mm)	INSTALLATION NOTES and WWW LINKS
Legs, 4 pack	1 pack per base cabinet	IKEA	AKURUM	Article Number : 300.763.19	Black	Diameter: 50 Min. height: 100 Max. height: 137	Product info: <a href="http://www.ikea.com/ca/en/catalog/products/30076319/">http://www.ikea.com/ca/en/catalog/products/30076319/</a> Please assemble and install according to the product manual that accompanies the product.  Each base cabinet needs 4 legs.
Plinth	4 in total (Estimated total plinth length for all base cabinets, incl. around the peninsula with some added spare length is 8000 mm)	IKEA	PERFEKT GNOSJÖ	Article Number : 902.204.65	Black, wood effect	Unit dims: Length: 2235 Height: 110 Thickness: 20	Product info: <a href="http://www.ikea.com/ca/en/catalog/products/90220465/">http://www.ikea.com/ca/en/catalog/products/90220465/</a> Please install according to the product manual that accompanies the product.  To be cut to exact size for each wall. For guidelines, please refer to the dimensions shown on Elevations K1 and K2, but please take exact measurements on the spot after all of the base cabinets have been installed, before cutting.  For the peninsula part that consists of a portion of the corner carousel cabinet connected to the oven base cabinet, please take exact measurements of all 3 sides on the spot for precise fitting of the plinths.
Handle - Small	6 (for base cabinets) See Sections 2 for quantities per cabinet	IKEA	KANSLI	Article Number : 002.222.23	Chrome	Length: 210 Width: 10 Depth: 28 Drilled hole diameter: 5 Hole spacing: 160	Product info: http://www.ikea.com/ca/en/catalog/products/0022223/
Handle – Large	11 (4 for base cabinets, 6 for wall cabinets, 1 for door of integrated dishwasher) See Sections 2, 3 and 6 for quantities per cabinet/door	IKEA	KANSLI	Article Number : 202.222.22	Chrome	Length: 383 Width: 10 Depth: 28 Drilled hole diameter: 5 Hole spacing: 320	Product info: http://www.ikea.com/ca/en/catalog/products/00222223/#/ 20222222
Suspension Rail	3 (Total length to accommodate all wall cabinets is estimated at 5717 mm)	IKEA	AKURUM	Article Number : 846.754.00	Grey, galvanized	Unit size: Length: 2030 Depth: 10 Height: 50	Product info: <a href="http://www.ikea.com/ca/en/catalog/products/84675400/">http://www.ikea.com/ca/en/catalog/products/84675400/</a> To be cut to size for each wall cabinet / cabinet combination. For the top 3 wall cabinets shown on [D12] Kitchen Elevation K2, 2 connected pieces of suspension rail can be used to hold the row.



Ria Thompson, DenDesignery +647 500 6518 ria@dendesignery.com www.dendesignery.com

#### **5 COVER PANELS for BASE CABINETS**

PRODUCT DI	PRODUCT DETAILS									
TYPE	QUANTITY	BRAND / SUPPLIER	NAME	CODE / REF	COLOUR / FINISH	DIMS INFO (mm)	INSTALLATION NOTES and WWW LINKS			
Cover Panel - standard size	1, for exposed right side of base oven cabinet	IKEA	PERFECT ABSTRAKT	Article Number : 502.008.79	High gloss cream	Unit size: Width: 626 Height: 771 Thickness: 14	Product info: <a href="http://www.ikea.com/ca/en/catalog/products/50200879/">http://www.ikea.com/ca/en/catalog/products/50200879/</a> Designated to cover the exposed right side of the base oven cabinet.			
Cover Panel - to be cut to size	1, for exposed back side of base oven cabinet and exposed back portion of the neighbouring carousel corner cabinet	IKEA	PERFECT ABSTRAKT	Article Number : 602.009.25	High gloss cream	Unit size: Width: 914 Height: 2438 Thickness: 16	Product info: <a href="http://www.ikea.com/ca/en/catalog/products/60200925/">http://www.ikea.com/ca/en/catalog/products/60200925/</a> To be cut to exact size. Estimated dimensions for this panel are 770H x 1060W. However, please take exact measurements on the spot before cutting and after all base cabinets and countertops have been installed. This cover panel is designated to cover the exposed back side of the oven cabinet together with the exposed portion of the neighbouring carousel cabinet for a seamless look.			
Cover Panel - to be cut into sizes for fillers	1, for filler pieces for gaps between base cabinets	IKEA	PERFECT ABSTRAKT	Article Number : 502.008.79	High gloss cream	Unit size: Width: 626 Height: 771 Thickness: 14	Product info: <a href="http://www.ikea.com/ca/en/catalog/products/50200879/">http://www.ikea.com/ca/en/catalog/products/50200879/</a> To be cut into precise sizes for any gaps between base cabinets.			

Note: All wall cabinets are to be installed without any side panels, i.e. the white frame sides are preserved to flow into the white walls.



Ria Thompson, DenDesignery +647 500 6518 ria@dendesignery.com www.dendesignery.com

### **6 APPLIANCES**

PRODL	PRODUCT DETAILS											
Ref ID within room	TYPE	QUANTITY	BRAND / SUPPLIER	NAME	CODE / REF	COLOUR / FINISH	DIMS INFO (mm)	REFERENCE DRAWING(S) for PLACEMENT	INSTALLATION NOTES and WWW LINKS  Please install according to the product manual that accompanies each product.			
12	Refrigerator	1	IKEA	DÅTID	Article Number: 502.038.73	Stainless Steel	Width: 900 Depth: 710 Height: 1745	(D11) Kitchen Elevation K1, (D1) Furnishing Layout – Ground Floor(Kitchen)	Product info: <a href="http://www.ikea.com/ca/en/catalog/products/50203873/">http://www.ikea.com/ca/en/catalog/products/50203873/</a>			
13	Integrated Dishwasher	1	IKEA	RENLIG	Article Number: 601.423.70	N/A (front to be covered with ABSTRAKT high gloss cream door)	Width: 610 Depth: 632 Height: 860	(D11) Kitchen Elevation K1, (D1) Furnishing Layout – Ground Floor(Kitchen)	Product info:  http://www.ikea.com/ca/en/catalog/products/60142370/ Please note that the product is shown with a black door at this link.  For this kitchen the door will be in ABSTRAKT high gloss cream. For door details:  http://www.ikea.com/ca/en/catalog/products/90200858/? query=902.008.58  The door requires 1 KANSLI handle - Large (Please see Section 4).  FIXA diffusion barrier shall be mounted above the dishwasher for added protection against moisture:  http://www.ikea.com/ca/en/catalog/products/04375085/			
14	Oven	1	IKEA	DÅTID	Article Number : 501.822.05	Stainless steel	Width: 755 Depth: 638 Height: 736	(D1) Furnishing Layout – Ground Floor(Kitchen)	Product info: <a href="http://www.ikea.com/ca/en/catalog/products/50182205/">http://www.ikea.com/ca/en/catalog/products/50182205/</a> This oven will be placed inside the Oven Base Cabinet (item ID8 in Section 2).			
15	Glass Ceramic Cooktop	1	IKEA	NUTID	Article Number : 101.826.17	Black	Width: 770 Depth: 541 Height: 76	(D1) Furnishing Layout – Ground Floor(Kitchen)	Product info: <a href="http://www.ikea.com/ca/en/catalog/products/10182617/">http://www.ikea.com/ca/en/catalog/products/10182617/</a> The hardwired installation of this cooktop must be executed by a qualified electrician – please ensure the kitchen fitters team includes this kind of specialist.  The cooktop is to be centered above the oven and its cabinet.			
16	Free- hanging extractor hood	1	IKEA	NUTID HDN SI850	Article Number : 101.423.58	Stainless steel	Width: 762 Depth: 400 Min. height: 800 Max. height: 1311 Chimney: 279W, 279D	(D1) Furnishing Layout – Ground Floor(Kitchen)	Product info: <a href="http://www.ikea.com/ca/en/catalog/products/10142358">http://www.ikea.com/ca/en/catalog/products/10142358</a> To be installed at its minimum height of 800 mm. To be centered above the cooktop for best performance.			



Ria Thompson, DenDesignery +647 500 6518 ria@dendesignery.com www.dendesignery.com

### 7 PLUMBING

PRODU	ICT DETA	AILS							
Ref ID within	TYPE	QUANTITY	BRAND / SUPPLIER	NAME	CODE / REF	COLOUR / FINISH	DIMS INFO (mm)	REFERENCE DRAWING(S)	INSTALLATION NOTES and WWW LINKS
room								for PLACEMENT	Please install according to the product manual that accompanies each product.
17	Sink	1	IKEA	BOHOLMEN 1 and ½ bowl inset sink with drainer	Article Number: 898.474.63	Stainless Steel	Length: 900 Depth: 500 Height: 180	(D11) Kitchen Elevation K1, (D1) Furnishing Layout - Ground Floor(Kitchen)	Product info: <a href="http://www.ikea.com/ca/en/catalog/products/S89847463/">http://www.ikea.com/ca/en/catalog/products/S89847463/</a> ATLANT strainer is included; for info and assembly instructions: <a href="http://www.ikea.com/ca/en/catalog/products/90056021/">http://www.ikea.com/ca/en/catalog/products/90056021/</a> To be installed with the drainer to the right, bowls to the left. To be fit inside the Base Cabinet for Sink (item ID4 in Section 2).  The sink has no pre-drilled holes for the faucet. Please refer to (D1) Furnishing Layout – Ground Floor(Kitchen) for intended faucet position. To make hole for the faucet IKEA's FIXA 2-piece tool set can be used: <a href="http://www.ikea.com/ca/en/catalog/products/28512100/">http://www.ikea.com/ca/en/catalog/products/28512100/</a>
18	Faucet	1	IKEA	LAGAN	Article Number : 700.850.29	Chrome plated	Height: 175 Connection length: 349	(D11) Kitchen Elevation K1, (D1) Furnishing Layout – Ground Floor(Kitchen)	Product info:  http://www.ikea.com/ca/en/catalog/products/70085029/  To be mounted in a 35 mm hole. Connection hoses with 9.5  mm connection included.  A tool that makes it easy to screw the kitchen faucet in place is included.



Ria Thompson, DenDesignery +647 500 6518 ria@dendesignery.com www.dendesignery.com

### **8 L-SHAPED CUSTOM COUNTERTOP**

PROD	UCT DETAILS								
Ref ID within room	TYPE / DESCRIPTION	QUANTITY	BRAND / SUPPLIER	NAME	COLOUR / FINISH	DIMS INFO, (mm)	REFERENCE DRAWING(S) for PLACEMENT	MEASURING and ORDERING NOTES	INSTALLATION NOTES and WWW LINKS
19	Laminate countertop: standard width, custom length, with cut-out for sink and a miter 45° cut at right end	1	IKEA	PERSONLIG made-to- measure	Black mineral effect	Width: 650 Thickness 38 mm Lengths and miter cut – estimated only: Wall edge L: 2765 Front edge L: 2115 Miter cut edge: 919.24	(D1) Furnishing Layout – Ground Floor(Kitchen)  (D11) Kitchen Elevation K1	Please take exact measurements for ordering the custom sized countertop after all base cabinets have been installed.  A cut-out for a BOHOLMEN sink [ID17 in Section 7] needs to be made in the countertop. The sink is to be installed above the base cabinet for sink [ID4 in Section 2]. Please take accurate measurements to specify this cut-out for the factory after the base cabinet for sink has been installed. The sink will be 100% watertight sealed to the custom-cut countertop at the factory and all will be delivered as one piece for installation.  To be ordered with square laminated edging strips (38 mm) in the same finish.	The 2 countertops (ID19 and ID20) are to be connected by a miter joint at the inside corner between the walls shown on Elevations K1 and K2.  Please ensure that the miter joint is 100% watertight sealed. Please use appropriate black sealant for a seamless finish.  Product info (for laminate finish): http://www.ikea.com/ca/en/catalog/products/10208783/ Info on PERSONLIG made-to-measure countertops: http://www.ikea.com/ms/en_CA/pdf/buying_guides/FY10/Countertops_Buying_Guide.pdf http://www.ikea.com/ms/zh_CN/pdf/20111_How_to_KI/
20	Laminate countertop, standard width, custom length, with miter 45 <sup>0</sup> cut at left end	1	IKEA	PERSONLIG made-to- measure	Black mineral effect	Width: 650 Thickness 38 mm Lengths and miter cut – estimated only: Wall edge L: 3800 Front edge L: 3150 Miter cut edge: 919.24	(D1) Furnishing Layout – Ground Floor(Kitchen) (D12) Kitchen Elevation K2	Please take exact measurements for ordering the custom sized countertop after all base cabinets have been installed.  This countertop is to be connected with a miter joint to Countertop ID19 at the inside corner between the walls shown on Elevations K1 and K2.  To be ordered with square laminated edging strips (38 mm) in the same finish.	WORKTOPS.pdf



Ria Thompson, DenDesignery +647 500 6518 ria@dendesignery.com www.dendesignery.com

#### 9 COUNTERTOP PENINSULA

PROD	UCT DETAILS								
Ref ID within room	TYPE / DESCRIPTION	QUANTITY	BRAND / SUPPLIER	NAME	COLOUR / FINISH	DIMS INFO, (mm)	REFERENCE DRAWING(S) for PLACEMENT	MEASURING and ORDERING NOTES	INSTALLATION NOTES and WWW LINKS
21	Laminate countertop, for peninsula – custom shape with rounded outside corners, with cut-out for cooktop	1	IKEA	PERSONLIG made-to- measure	Black mineral effect	Thickness 38 mm Total Length (from countertop ID20 out): 2100 Width1: 800 at Length1: 750 Width2: 1000 at Length2: 1350  Please see drawing for shape and orientation of the peninsula design.	(D1) Furnishing Layout – Ground Floor(Kitchen)	A cut-out for a NUTID Ceramic cooktop [ID15 in Section 6] needs to be made in the countertop. The cooktop is to be installed above the base cabinet for oven [ID8 in Section 2]. Please take accurate measurements to specify this cut-out for the factory after the base cabinet for oven has been installed.  For ordering this made-to-measure countertop please provide all of the following:  1. The exact measurements (taken as advised above) for the cooktop cut- out.  2. A copy of the (D1) Furnishing Layout – Ground Floor(Kitchen) drawing where all other necessary dimensions are shown, including radius info for the rounded corners [R300 mm for all 3 corners].  3. This specification section.  To be ordered with square laminated edging strips (38 mm) in the same finish.	Important installation note: The kitchen peninsula portion that contains the oven and its base cabinet is to be attached to the floor. Due to the Kährs wood floor being in a floating installation, this kitchen unit cannot be fixed to the floor planks. Instead, it must be fixed through the floor allowing space to prevent the fixed object from pressing down on and trapping the floor. There must be a movement joint around the space. Please follow the recommendations outlined here: http://www.kahrs.com/Global/PDF/Kahrs_Installation_Woodloc5S_Floating_EXP.p. df for proper handling of this issue.  Please ensure that the joint with countertop ID20 is 100% watertight sealed. Please use appropriate black sealant for a seamless finish.  Product info (for laminate finish): http://www.ikea.com/ca/en/catalog/products/10208783/Info on PERSONLIG made-to-measure countertops: http://www.ikea.com/ms/en_CA/pdf/buying_guides/FY10/Countertops_Buying_Guide.pdf http://www.ikea.com/ms/zh_CN/pdf/20111_How_to_KI/WORKTOPS.pdf
22	Legs	2	IKEA	VIKA BYSKE	Chrome plated	Diameter: 60 Min. height: 700 Max. height: 1070	(D1) Furnishing Layout – Ground Floor(Kitchen)	For proper weight support of the breakfast bar portion of the peninsula, 2 legs are required. They are to installed at 2 the rounded corners furthest from the cabinet support, 300 mm from each countertop edge. To view the positions, please refer to the (D1) Furnishing Layout – Ground Floor(Kitchen) drawing.	Product info: http://www.ikea.com/ca/en/catalog/ products/84609085/ Please attach each leg according to the installation instructions provided with the product. The legs are adjustable in height. Please set both heights appropriately to ensure level surface of the breakfast bar.



Ria Thompson, DenDesignery +647 500 6518 ria@dendesignery.com www.dendesignery.com

#### 10 BACKSPLASH

PROD	UCT DETAILS	3							
Ref ID within room	TYPE	QUANTITY	BRAND / SUPPLIER	NAME	CODE / REF	COLOUR / FINISH	DIMS INFO (mm)	REFERENCE DRAWING(S) for PLACEMENT	MEASURING and INSTALLATION NOTES, WWW LINKS
23	Backsplash, PVCu Hygienic Cladding (custom size)	2 (one for wall K1, and one for wall K2)	Altro	Altro Whiterock Chameleon	6618	Moulin Rouge (Red, gloss)	Thickness: 2.5 mm  Estimated: Height: 180 mm Width for wall on (D11) Kitchen Elevation K1: 2765 Width for wall on (D12) Kitchen Elevation K2: 3800	(D11) Kitchen Elevation K1, (D12) Kitchen Elevation K2  (D5) Painter/ Decorator/Installer - Ground Floor	Please use the estimated measurements as a guideline. Accurate measurement for ordering the 2 custom sized backsplash boards are to be taken on the spot after all base cabinets and countertops have been installed.  Product info: http://www.altro.co.uk/Wall-Cladding/Hygienic-Wall-Cladding/Altro-Whiterock-Splashbacks.aspx Data sheet: http://www.altro.co.uk/getmedia/72e037ce-f108-4d1d-9c45-7d1cfa0999e4/Altro-Whiterock-Chameleon-W160-161-Data-Sheet.pdf.aspx Installation Instructions: http://www.altro.co.uk/getmedia/07a26c24-d44f-442c-b034-a6b595aaa654/Altro-Technical-Installation-Guide-WAAltro-Whiterock.pdf.aspx Adhesive Guide: http://www.altro.co.uk/getmedia/ca269093-ac81-4c9f-b56a-10f12816847f/Altro-Technical-Data-Sheet-Adhesive-Information-(inc-Nuvola).pdf  Installation of the backsplash boards is to take place after all wall painting and cabinet/countertop installations have been completed. Please use Altro colour-matched sealant to ensure watertight seams at the inside corner where the 2 backsplash boards (wall K1 and wall K2) are to connect, and also with all wall and countertop surfaces.